



Gardall's Single Door Depositories

Visit us online at
www.gardall.com



Designed to protect money collection where immediate deposit is required. Deposit can be made into the safe while the door is locked. Exclusive baffle design prevents contents from being removed through the entry opening. Hopper rotor is built into safe body and cannot be removed to gain access to the safe.

Heavy Duty Depositories Standard Design Benefits

- CLASS B Insurance Rating – 1/2" steel door with punch resistant bolt and relocking device to deter forcible entry. 1/4" steel body construction.
- Dual Custody Key Locks – Requires 2 keys to open door for absolute security.
- UL listed, S&G Group II combination lock.
- Triple boltwork with independent relocking device.
- Relocking device – If back cover is knocked off of lock, the independent relock device is activated, preventing bolt withdrawal. Available on either combination or dual key operated doors.

- Rotary Hopper Capacity – 3¾" x 9" x 4" designed to fit most standard money bags and envelopes.
- Front Loading Capacity – designed to fit most large money bags – 2¾" x 10½" x 7½"
- Interchangeable Doors – 2 sizes 9" x 9" and 12" x 12".
- 4 anchoring holes in base.

Standard color: Gray

All specifications are subject to change without notice.

To Operate Front Loading Depository

Pull drop door forward, place items to be deposited inside, release the drop door. Deposited item should drop inside. Open the drop door to be certain.

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Door Size	Approx. Weight (lbs.)	
	H	W	D	H	W	D				
FL1218	18"	11½"	13"	10½"	10¾"	10¾"	1213	9" x 9"	103	
FL1328	25"	14½"	13"	15"	13½"	11½"	2329	12" x 12"	165	
BL1328	25"	14½"	13"	15"	13½"	11½"	2329	12" x 12"	150	
RC1237	36¾"	14½"	13"	T	15¼"	13¾"	10¾"	2180	12" x 12"	220
				B	14¾"	13¾"	10¾"	2180		
*BL1337	36½"	14½"	13"	T	12"	13½"	10¾"	1742	12" x 12"	215
				B	13¾"	13¾"	10¾"	2032		

Above available as (K) dual key lock (C) Group II combination lock, (KO) key-op lock or (E) S&G 6120 electronic lock. Please specify.

*BL designates depository on back side of safe from door. Add 2" to outside depth for dial and handle.

IMPORTANT! These safes are built with the intent of keeping large bills and valuables out of unprotected areas, until deposits can be made. They are not meant to be used as unprotected storage safes for overnight, or lengthy periods of time. Discuss your needs with your local safe professional or if you are in doubt, call GARDALL and we will recommend a safe expert.